

Technocraft Industries (India) Ltd.

Titeseal Closure Product Data Sheet 63mm Canseal Closures

General Information

- Raw Material : Polyethylene
- Fits on both Metal and Plastic tops.
- Fits on a large opening without registry, thus allows a fast and efficient filling.
- One time double tamper proof sealing.
- Use Anti-Glug for easy and efficient pouring for viscous fluids.
- Suits upto 5 gallon pails
- Technocraft Canseal can also be printed with your company logo or message about the drum contents.
- Packing: Sealed in Polythelene bag and packed in corrugated box.

Types of Canseal closures



Standard 63C-STA



ANTI-Glug with Decorative Tamper-Proof Cap 63C-AGLDC



Anti-Glug 63C-AGL



Standard with Aluminium
Tamper-Proof Cap
63C-STAL



Standard with Decorative Tamper-Proof Cap



ANTI-Glug with Aluminium Tamper-Proof Cap



VENT Version

Standard Packing

			_		
	Item	Box	Box Size (mm)	Pallet	Pallet
		Quantity		Quantity	Size
	63mm				
	Canseal	600	560 x 360x 380	10800	44" x 44"

- Boxes are marked with item code.
- Pallets are stretch wrapped.
- Optional Special packaging as per customer's requirement.

Metal Drum Top Opening Tools for Canseal Closures

A set of two press tools "Stage-one" and "Stage-two" supplied by Technocraft are to be used to make the opening for Canseal closures in the sheet metal drum top. These tools are supplied by Technocraft and can be loaded on a power press. There are adjustable stoppers in "Stage-one" press tool, which are to be set to position the opening for Technocraft Canseal closure drum top. Pressure pad and stripper shall be supplied to suit the cross sectional geometry of the users drum top.

"Stage-one" press tool is a combination tool and performs piercing and forming operation.

"Stage-two" press tool does the curling operation.





Crimping Tools for Canseal Closures

Either a manual or a pneumatic crimping tool is to be used to fix the canseal closure on a drum top. These crimping tools supplied by Technocraft are common for metal drum tops and plastic drum top





 More information can be availed by <u>clicking here</u> or by contacting our head quarters as per details on our web page.